IN THE CLAIMS:

Please amend the claims as follows. Please add new claim 29.

Claims 1-8. (Cancelled)

9. (Currently Amended) A method for improving the reliability of a computer system including a bus and plug-in units coupled thereto, comprising:

~~Connecting~~ connecting at least one ~~each~~ plug-in unit to ~~the~~a bus via a separate interface circuit corresponding thereto;

addressing a respective plug-in unit, via the bus, by addressing operations directed at said respective plug-in unit and which are monitored locally by said interface circuit corresponding thereto;

performing a time duration operation of addressing of said plug-in unit; and

checking the state of addressing of the addressed plug-in unit such that (i) when the addressing is ended before expiration of a predetermined period of time, the time duration operation of addressing is terminated and a new time duration operation of addressing is set to commence at time of next occurrence of addressing, and (ii) when the duration operation of addressing exceeds the predetermined time period, the addressing to that plug-in unit is terminated by said interface circuit corresponding thereto by sending into the bus a signal indicating termination of addressing.

10. (Previously presented) A method as defined in claim 9, wherein:

the time duration of addressing is monitored using a watchdog timer with a predetermined timing set therein.

11. (Previously presented) A method as defined in claim 9, wherein:

when addressing is terminated an error signal is set by the interface circuit into an active state in the bus.

12. (Previously presented) A method as defined in claim 9, wherein:

when addressing is terminated an error signal indicating an error condition in the plug-in unit is set by the interface circuit into an active state in the status register of the plug-in unit.

13. (Currently Amended) An interface circuit for providing local monitoring capability to a plug-in unit of a computer system, ~~including a bus and plug-in units coupled to said bus, wherein a separate interface circuit is provided to connect each of said plug-in units to said bus and~~ comprising:

a watchdog timer;

first means for activating the watchdog timer upon start of an addressing operation directed to the plug-in unit corresponding thereto; and

second means for sending into t̶h̶e̲a̲ bus a signal indicating termination of addressing, the termination of addressing being effected when the duration of said addressing exceeds a predetermined time duration for addressing, as measured by the watchdog timer.

14. (Currently Amended) An interface circuit as defined in claim 13, further comprising:

means for setting an error signal into an active state in t̶h̶e̲a̲ bus.

15. (Currently Amended) An interface circuit as defined in claim 13, further comprising:

means for setting a signal indicating an error condition in t̶h̶e̲a̲ plug-in unit into an active state in a status register of the plug-in unit.

16. (Currently Amended) An interface circuit as defined in claim 14, further comprising:

means for setting a signal indicating an error condition in t̶h̶e̲a̲ plug-in unit into an active state in a status register of the plug-in unit.

17. (Previously presented) An interface circuit as defined in claim 13, wherein:
the bus is a Compact PCI bus.

18. (Previously presented) An interface circuit as defined in claim 16, wherein:

the bus is a Compact PCI bus.

19. (Cancelled)

20. (Currently Amended) A method according to claim 10, wherein:

said watchdog timer is provided at each said interface circuit or at each said of at

least one plug-in unit.

21. (Previously Presented) A computer system including a bus and plug-in units

coupled thereto, wherein the computer system comprises:

a plurality of interface circuits and a plurality of plug-in units each of which is

connected to said bus via a separate one of said interface circuits further corresponding

thereto, wherein each of said interface circuits comprises:

a watchdog timer;

first means for activating the watchdog timer upon start of an addressing operation

directed to the plug-in unit corresponding thereto; and

second means for sending into the bus a signal indicating termination of

addressing, the termination of addressing being effected when the duration of said

addressing exceeds a predetermined time duration for addressing, as measured by the watchdog timer.

22. (Previously presented) A computer system according to claim 21, wherein each said interface further comprises:

means for setting an error signal into an active state in the bus.

23. (Previously presented) A computer system according to claim 22, wherein each said interface circuit comprises:

means for setting a signal indicating an error condition in the corresponding plug-in unit into an active state in a status register of the plug-in unit.

24. (Previously presented) A computer system according to claim 23, wherein:

the bus is a Compact PCI bus.

25. (Previously presented) A computer system according to claim 21, wherein each said interface circuit comprises:

means for setting a signal indicating an error condition in the corresponding plug-in unit into an active state in a status register of the plug-in unit.

26. (Previously presented) A computer system according to claim 21, wherein:

the bus is a Compact PCI bus.

27. (Cancelled)

28. (Previously presented) A computer system according to claim 27, wherein:

the bus is a Compact PCI bus.

29. (New) An interface circuit for providing local monitoring capability to a plug-in unit of a computer system, comprising

a bus and plug-in units coupled to the bus;

a separate interface circuit connecting each of the plug-in units to the bus;

a watchdog timer;

an activating device configured to activate the watchdog timer upon start of an addressing operation directed to the plug-in unit corresponding thereto; and

a sending device configured to send a signal into the bus indicating termination of addressing, the termination of addressing being effected when the duration of said addressing exceeds a predetermined time duration for addressing, as measured by the watchdog timer.